

Advanced Boiling Water Reactor (ABWR)

Technology, Schedule, and Cost Confidence


The Advanced Boiling Water Reactor (ABWR) is the foundation of GEH's nuclear reactor portfolio. The Gen III design is available today to meet power generation needs ranging from 1350 to 1460 MW net. It delivers proven advanced technology and competitive economics.

ABWR already has an impressive track record. It is the world's first and only Generation III nuclear plant design in operation today, providing the benefit of a combined 20 reactor-years of operational experience. GEH's first ABWR began commercial operation at Kashiwazaki-Kariwa in Japan, in 1996. Three additional ABWRs are operating in Japan with two more under construction in Japan, and two in Taiwan. The ABWR is licensed in the U.S., Japan and Taiwan.

The ABWR is a direct cycle Light Water Reactor that reflects 50 years of continued evolution from GEH's initial BWR concept—combining the best features from our worldwide BWR fleet. Our well-established, global supply chain is already qualified and prepared today to support deployment of new nuclear power plants.

Benefits and Features of the ABWR

- Lowest-in-Class core damage frequency at power (1.6×10^{-7} /year)
- Standardized design capable of further uprates
- 60-year Design life
- Modularized design to optimize construction schedule
- Demonstrated capital and O&M cost structure in Japan
- Significantly lower in staffing and maintenance costs per kWh than the current U.S. installed base of Gen I and II nuclear reactors



Simpler yet Safer Design with Advanced Technology

- **Reactor internal pumps** – eliminates external recirculation systems
- **Integrated containment and reactor building** – improved seismic response, compact, and easier to construct
- **Compact reactor building** – less construction material and shorter construction times
- **Optimized modularization** – module designs refined and proven in real installations
- **Sophisticated control systems** – fully digital, providing reliable and accurate plant monitoring, control, and diagnostics
- **High integrity fuel, improved water chemistry, and radiation source elimination** – reduced radwaste and occupational exposure




HITACHI

a product of
ecomagination

ABWR Plant Layout

- | | | |
|--|--|----------------------------------|
| 1. Reactor Pressure Vessel | 17. RCIC Steam Turbine and Pump | 27. Main Control Room |
| 2. Reactor Internal Pumps | 18. Diesel Generator | 28. Turbine-Generator |
| 3. Fine Motion Control Rod Drives | 19. Standby Gas Treatment Filter and Fans | 29. Moisture Separator Reheater |
| 4. Main Steam Isolation Valves | 20. Spent Fuel Storage Pool | 30. Combustion Turbine Generator |
| 5. Safety/Relief Valves (SRV) | 21. Refueling Platform | 31. Air Compressor and Dryers |
| 6. SRV Quenchers | 22. Shield Blocks | 32. Switchyard |
| 7. Lower Drywell Equipment Platform | 23. Steam Dryer and Separator Storage Pool | |
| 8. Horizontal Vents | 24. Bridge Crane | |
| 9. Suppression Pool | 25. Main Steam Lines | |
| 10. Lower Drywell Flooder | 26. Feedwater Lines | |
| 11. Reinforced Containment Concrete Vessel | | |
| 12. Hydraulic Controls Units | | |
| 13. Control Rod Drive Hydraulic System Pumps | | |
| 14. RHR Heat Exchanger | | |
| 15. RHR Pump | | |
| 16. HPCF Pump | | |



HITACHI

For more information, contact your GE Hitachi Nuclear Energy sales representative or visit us at www.ge-energy.com/nuclear

Copyright © 2010 GE Hitachi Nuclear Energy. All Rights Reserved.

GEA14576H